

STAX®



SRM-D10 II

Amplifier (SRM-D10 II)

Elevate Your Listening Experience to Unprecedented Heights



The STAX SRM-D10 II electrostatic headphone amplifier redefines audio excellence by combining cutting-edge technology and superior craftsmanship. Designed to provide audiophiles and professionals with the ultimate sound experience, the SRM-D10 II boasts a range of exceptional features:

FEATURES

- Enhanced Sound Quality:** The SRM-D10 II utilizes hardware decoding and high-quality audio capacitors to deliver unparalleled sound quality, ensuring every note is crisp and every detail is vivid.
- DSD and PCM Support:** With support for DSD sampling rates up to DSD256 and PCM sampling rates up to 384kHz/32bit, the SRM-D10 II can faithfully reproduce high-resolution audio formats, preserving the artist's original intention.
- High-Quality Power Amplifier:** The SRM-D10 II is equipped with a high-quality power amplifier, providing outstanding performance and remarkable power, allowing you to experience music in its purest form.
- High Voltage Output:** A robust DC 580V DC bias enhances the amplifier's output, resulting in a more dynamic and powerful soundstage.
- Rugged Aluminium Alloy Shell:** The aluminium alloy shell not only exudes a sleek, modern design but also offers higher strength and corrosion resistance, ensuring the SRM-D10 II is built to last.
- Versatile Connectivity:** The SRM-D10 II supports both USB digital and 3.5mm analog audio inputs, offering flexibility in connecting to a wide range of devices.
- Compatibility:** Designed to complement all STAX PRO-type headphones, the SRM-D10 II ensures that you can enjoy the full potential of your earspeakers.

SPECIFICATIONS

Rated input level:	230mV (100V output)
Maximum input level:	10V (minimum volume in Line In input)
Gain:	53dB (450 times)
Harmonic distortion:	≤0.025% / 1kHz-10kHz
Input impedance:	10KΩ (Line In input)
Maximum output voltage:	200Vr.m.s / 100Hz-10kHz
Supply voltage:	DC 5V/9V/12V/15V
Power consumption:	6.4W (USB input) 5W (Line In input)
DSD Support:	Up to DSD256
PCM Support:	Up to 384kHz/32bit
Amplifier:	High-Quality Power Amplifier
Output Bias:	DC 580V
Shell Material:	Aluminium Alloy
Input Options:	USB Digital, 3.5mm Analog
Compatibility:	Suitable for all STAX PRO-type headphones

Package Contents:

STAX SRM-D10 II Electrostatic Headphone Amplifier
Power Cable
User Manual

Rediscover the magic of your favourite music with the STAX SRM-D10 II. Elevate your audio experience with high-resolution sound, precision engineering, and unmatched performance.

Immerse yourself in music the way it was meant to be heard

STAX Limited
www.staxheadphones.com
3798-1 Shimonanbata
Fujimi-shi, Saitama-pref
Japan 354-0004